



JUMP STARTER SOS BOOSTER[®] SOS 24V-1200CA

APPLICATIONS



| MOTOR | |
|----------|-----|
| Vehicle | 24V |
| Gasoline | ✓ |
| Diesel | ✓ |

| TYPE OF RECOVERY |
|--|
| 24V vehicles: intensive |
| Laborious starts, recovery of a vehicle with completely flat battery |
| Successive jump starts, several times during the day |
| Jump start of vehicles' fleets |
| Difficult conditions of use* |



The correct use of a Ceteor Booster cannot cause any damage to the electronic of a vehicle..


Ceteor booster packs are perfectly compatible with hybrid vehicles.

* Extreme conditions of use such as frost, extreme heat...

| TYPE OF VEHICLES TO BE JUMP STARTED |
|-------------------------------------|
| Heavy civil engineering equipment |
| New and second-hand truck |
| New and second-hand bus and coach |
| Leisure plane, propeller |
| Leisure boat |
| Locomotive |

Diesel motors up to*:

| POWER IN HP | | | | |
|-------------|-----|-----|------|------|
| 100 | 250 | 500 | 1000 | 1500 |



 Normal
 Intensive



Following the principle "who can do more can do less" our most powerful battery boosters can also be convenient for the applications covered by less powerful battery boosters with same voltage of our range.

Caution :

The circumstances/conditions when starting a vehicle depend of various parameters: vehicle's condition, engine type (petrol or diesel) and power, presence of battery in vehicle or not, temperature, frequency of use ... Those influence the jump start's facility. *Chart for your information - Manufacturer's advice.*

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|--------------------|
| Reference | 760005 |
| Voltage | 24V |
| Cranking Amps | 1200 A |
| Peak Amps | 3100 A |
| Nr of batteries | 2 |
| Starting cable length | 1,35 m |
| Starting cable diameter | 50 mm ² |
| Type of clamps | 850 A |
| Clamps length | 215 mm |
| Clamps opening | 54 mm |
| AC/DC* charger | 4A |
| Cable to charge DC/12V | ✘ |
| 12V Output | ✘ |
| Reverse polarity signal | ✔ |
| Internal fuse | 500 A |
| Connector for auxiliary cables | ✔ |
| Net weight | 24,8 kg |
| Dimensions (cm) | 53 x 16 x 48 |
| Gross weight | 28,5 kg |
| Packing dimensions (cm) | 56 x 19 x 60,5 |

-  Yes
-  No
-  Option
-  Upon request

STANDARD EQUIPMENT



LED CLAMPS

The blue clamp is equipped with a led (lamp) for an easier and safer use, especially in the dark.



AUXILIARY CONNECTOR & SWITCH - REVERSE POLARITY SIGNAL

This booster is equipped as a standard with a switch and a reverse polarity signal to improve security during use. The switch is made of a red tension selector, which can be used to plug in specific auxiliary cables with NATO, Park plug, etc.